

Specifications

Models	GS-1530		GS-1532		GS-1930		GS-1932	
Measurements	Metric	US	Metric	US	Metric	US	Metric	US
Working height maximum*	6.40 m	20 ft 11 in	6.40 m	20 ft 11 in	7.60 m	24 ft 11 in	7.60 m	24 ft 11 in
Platform height maximum w/load sense	4.40 m	14 ft 5 in	4.40 m	14 ft 5 in	5.60 m	18 ft 5 in	5.60 m	18 ft 5 in
Platform height - stowed	0.97 m	3 ft 2.2 in	0.97 m	3 ft 2.2 in	1.00 m	3 ft 3.5 in	1.00 m	3 ft 3.5 in
Platform length - outside	1.63 m	5 ft 4 in						
extended	2.54 m	8 ft 4 in						
Slide-out platform extension deck	0.91 m	3 ft						
Platform width - outside	0.74 m	2 ft 5 in						
Guardrail height	1.10 m	3 ft 7 in						
Toeboard height	0.15 m	6 in						
Height - stowed: folding guardrails	2.03 m	6 ft 9 in	2.03 m	6 ft 9 in	2.11 m	6 ft 11 in	2.11 m	6 ft 11 in
rails folded	1.73 m	5 ft 8 in	1.73 m	5 ft 8 in	1.75 m	5 ft 9 in	1.75 m	5 ft 9 in
Length - stowed	1.83 m	6 ft						
Length - stowed extended	2.74 m	9 ft						
Width	0.76 m	2 ft 6 in	0.813 m	2 ft 8 in	0.76 m	2 ft 6 in	0.813 m	2 ft 8 in
Wheelbase	1.32 m	4 ft 4 in						
Ground clearance - center	6 cm	2.4 in						
- with pothole guards deployed	2 cm	0.75 in						

Productivity

Max platform occupancy (in/out) ¹	2/-		2/1		2/-		2/1	
Lift capacity	272 kg	600 lbs	272 kg	600 lbs	227 kg	500 lbs	227 kg	500 lbs
Drive speed - stowed	4.0 km/h	2.5 mph						
Drive speed - raised	0.8 km/h	0.5 mph						
Gradeability - stowed**	30%	30%	30%	30%	25%	25%	25%	25%
Turning radius - inside	zero	zero	zero	zero	zero	zero	zero	zero
Turning radius - outside	1.55 m	5 ft 1 in						
Raise / lower speed	16 / 29 sec	16 / 29 sec	16 / 29 sec	16 / 29 sec	16 / 29 sec	16 / 29 sec	16 / 29 sec	16 / 29 sec
Controls	proportional		proportional		proportional		proportional	
Drive	dual front wheel							
Multiple disc brakes	dual rear wheel							
Tyres - solid non-marking	30x11x20 cm 12x4.5x8 in							

Power

Power source	24 V (four 6 V 225 Ah batteries)							
Hydraulic system capacity	14.2 L	3.75 gal	14.2 L	3.75 gal	14.2 L	3.75 gal	14.2 L	3.75 gal

Sound & Vibration Levels


Sound pressure level (ground workstation)	<70 dBA	<70 dBA						
Sound pressure level (platform workstation)	<70 dBA	<70 dBA						
Vibration	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²

Weight***

	1,233 kg	2,718 lbs	1,269 kg	2,797 lbs	1,498 kg	3,302 lbs	1,503 kg	3,313 lbs
--	----------	-----------	----------	-----------	----------	-----------	----------	-----------

Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013); 2004/108/EC (EMC); 2006/95/EC (LVD)



¹ Indoor use only for the 30' Series
^{*} The metric equivalent of working height adds 2 m to platform height.
^{**} Gradeability applies to driving on slopes, see Operator's Manual for details regarding slope ratings.
^{***} Weight will vary depending on options and/or country standards.

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
<p>Measurements</p> <p>GS-1530 & GS-1532</p> <ul style="list-style-type: none"> 6.40 m (20 ft 11 in) working height Up to 272 kg (600 lbs) lift capacity <p>GS-1930 & GS-1932</p> <ul style="list-style-type: none"> 7.60 m (24 ft 11 in) working height Up to 227 kg (500 lbs) lift capacity <p>Productivity</p> <ul style="list-style-type: none"> Folding rails with half-height swing gate Smart Link™ control system (joystick, 2 lift speeds & 2 selectable proportional drive speeds, user-friendly diagnostics) Rear recessed charger receptacle Platform control with battery charge indicator On-board diagnostic system AC power to platform Lanyard attachment points Manual platform lowering valve Emergency stop at both platform and ground controls Rear wheel multiple disc brakes Front wheel hydraulic dynamic braking Manual brake release Swing-out component trays Pothole guards Tilt level sensor with audible alarm Descent alarm Flashing beacons Electronic horn Hour meter Certified load sensor Telematics-Ready Connector <p>Power</p> <ul style="list-style-type: none"> 24 V DC battery pack Universal 20 amp smart charger 	<p>Platform</p> <ul style="list-style-type: none"> 1.63 x 0.74 m (5 ft 4 in x 2 ft 5 in) steel platform 0.91 m (3 ft) slide-out extension deck <p>Power</p> <ul style="list-style-type: none"> 24 V DC (four 6 V 225 Ah batteries) <p>Drive</p> <ul style="list-style-type: none"> Dual front wheel drive <p>Tyres</p> <ul style="list-style-type: none"> Solid non-marking 	<p>Productivity Options</p> <ul style="list-style-type: none"> Air line to platform Power to platform (incl. plug, socket and ground fault interrupt leakage on request) Biodegradable hydraulic oil⁽²⁾ Track & Trace⁽¹⁾ (GPS unit providing machine location & operating information) Motion alarm package Automotive horn <p>Power Options</p> <ul style="list-style-type: none"> Maintenance-free batteries Low-temperature cut-out module⁽³⁾



⁽¹⁾ Includes a first 2 years subscription
⁽²⁾ Available on selected models only. See your Genie representative for further information.
⁽³⁾ For outdoor models only

United Kingdom

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334, Email AWP-InfoEurope@terex.com
 Visit www.genielift.co.uk/locations to view our global locations list.

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2016 Terex Corporation.

